

WASHING BRUSH FOR AUTOMATIC MOTOR VEHICLE WASHING SYSTEMS

BACKGROUND OF THE INVENTION

5

The present invention relates to a washing brush to be applied to washing brush assemblies in automatic systems for washing motor vehicles in general.

10

As is known, automatic systems for washing motor vehicles in general conventionally comprise washing brushes, which are made by coupling, in an axial direction, a plurality of brush elements which are substantially constituted by a cylindric body thereon are coupled band elements comprising cleaning elements formed of a felt or a like material, or a foamed plastics material.

15

With reference to the diagram shown in figure 1, the band elements 1, which are arranged with a substantially vertical arrangement, i.e. parallel to the axis of the cylindric body, provide a vertical discontinuous arrangement perpendicular to the brush movement direction.

20

In such an arrangement, the controlling motors are supplied with alternating pulses, the uneven amplitudes or values of which make difficult to hold the washing brush in a stable contact condition against the working surface therefor.

25

Accordingly, the contact gaps provide an objectable noise for a person inside the motor vehicle.

30

Moreover, it is necessary to frequently

adjust the revolution number of the cleaning brush depending on the motor vehicle transiting speed, in order not to leave uncleaned regions along the motor vehicle itself.

5 Yet another drawback is that, during the rotation of the brush, a person can easily see the central body or tube supporting the cleaning elements, thereby the bush construction appears as a scarcely dense construction, which negatively affects
10 the operating properties of the product.

Yet another drawback is that interspaces are inevitably formed between the several cleaning elements, with a consequent formation of contact lacking spaces on the surfaces to be washed.

15 Moreover, prior washing brushes generate packaging and transport problems, since it is not possible to provide the cleaning band elements in an ordered manner without bending them according to a small angle thereby frequently deforming the band
20 materials which could render the band elements nearly unusable.

Thus, the packaging cost is inevitably very high.

25

SUMMARY OF THE INVENTION

The aim of the invention is to overcome the above mentioned drawbacks, by providing a washing brush, to be applied to brush assemblies in automatic
30 systems for washing motor vehicles in general, in which the band elements can be arranged in a much more rational manner so as to eliminate possible

interspaces causing contact lackings on the motor vehicle being washed, thereby improving the washing quality.

Within the scope of the above mentioned
5 aim, a main object of the present invention is to provide such a washing brush in which, the number of the cleaning elements contacting the surface to be cleaned being the same, is possible to reduce the number of the band elements or assemblies to be
10 connected to the brush central body or tube.

Yet another object of the present invention is to provide such a washing brush in which the cleaning band elements and related terminal cords can be properly oriented thereby drastically reducing the
15 volume of the washing brush, so as to facilitate the packaging operations.

Yet another object of the present invention is to provide such a washing brush which, owing to its specifically designed features, is very reliable
20 and safe in operation.

According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by a washing brush
25 for washing brush assemblies to be applied to automatic systems for washing motor vehicles in general, comprising a cylindric body on the side outer surface thereof are provided a plurality of band elements defining the cleaning elements of said
30 washing brush, characterized in that said band elements extend on the side surface of said cylindric body along directions which are inclined with respect

to the axial direction.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Further characteristics and advantages of the present invention will become more apparent hereinafter from the following detailed disclosure of a preferred, though not exclusive, embodiment of a washing brush to be applied to washing brush
10 assemblies of automatic systems for washing motor vehicles in general, which is illustrated, by way of an indicative, but not limitative, example, in the accompanying drawings, where:

Figure 1 shows a washing diagram which can
15 be obtained by washing brushes according to the prior art;

Figure 2 is a schematic perspective view illustrating a washing brush, having applied, schematically, only two band elements;

20 Figure 3 is an elevation view illustrating the washing brush shown in figure 2;

Figure 4 is a further schematic elevation view illustrating a washing brush assembly made by axially connecting several washing brushes;

25 Figure 5 is a further schematic view illustrating a band element;

Figure 6 shows the arrangement of the band elements designed for reducing the packaging size thereof; and

30 Figure 7 shows a dynamic operating diagram of the subject washing brush, during a motor vehicle washing operation.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to the number references of the above mentioned figures, the washing brush according to the present invention, which has been generally indicated by the reference number 10, comprises a cylindric body 11, of a per se known type, on the side surface thereof are provided a plurality of band elements 12.

The band elements 12, in particular, are advantageously made by using a plate-like element of a closed cell foamed material, or an open-cell foamed material or, optionally, a felt material.

The band elements 12 comprise a plurality of longitudinal slits 13, defining a plurality of strips 14, constituting the cleaning elements of the washing brush.

The main feature of the invention is that the band elements arranged on the side surface of the cylindric body 11 are inclined with respect to the axial direction of said cylindric body.

Thus, in actual practice, the band elements will assume a diagonal arrangement or position, allowing the band elements to be arranged in a very rational manner, to provide a very good distribution of the washing bristles, the number of the washing assemblies being the same.

Moreover, the slanted arrangement of the bristles, which can be coupled to the cylindric body 11 by any suitable coupling means, allows to provide a longer band element, having a length larger than that of a band element arranged in a direction

THIS PAGE BLANK (USPTO)

parallel to the axis.

According to a preferred inclination, the band element has in average a 25% larger length.

In this connection it should be pointed out that the inclination of the band elements can be further changed, to also provide further larger lengths.

Accordingly, the amount of material being the same, the number of the band elements will be smaller, since each band element will have a width larger than the widths of the band elements arranged parallel to the axis, and accordingly perpendicularly to the motor vehicle to be washed motion direction.

Accordingly, the reduction of the number of
is the band elements will reduce the labor necessary for
making the single components on the washing brush and
for fixing them, independently from the method for
carrying out the fixing operation.

Moreover, the slanted or diagonal arrangement allows the orienting of the band elements and related end/^{cleaning}strips/^{or brushes} to be offset, notwithstanding a radial effect provided by the centrifugal force.

25 Actually, in automatic motor vehicle washing systems, the maximum speed does not exceed 110 rpm's and the natural trend of the band elements to fall in a natural direction due to their oblique positions, allows said band elements to "close" possible spaces or gaps, in an optimum manner.

Moreover, the colored spiral obtained by adjoining different colors on the band elements would be perfectly arranged with respect to its epicycloidal pattern.

* Advantageously each band element is engaged in a corresponding diagonal separated slanted re-entrant on the outer surface of the cylindric body 11, of substantially V-shape and, as in particular shown in fig. 1, the clearing strips 14 or bristles are defined by different slots or cuts longitudinally parallelly extending thereon each band element.

THIS PAGE BLANK (USPTO)

Furthermore, the slanted position of the band elements with the washing brush assembly arranged in a vertical position, in a stop condition thereof, will allow the band elements to fall in an ordered manner by automatically overlapping one another, thereby the brush assembly can be packaged with a comparatively small size, without damaging the product in its packaged condition.

Thus, by greatly reducing the packaging requirements, it would be possible to control in an optimum manner the required packaging volumes, with a reduction of the transport expenses of about 300%.

Moreover, the slanted arrangement of the band elements provides an upward or downward directed entraining effect thereon, since their natural opening movement is not perpendicular to the axis of the cylindric body the band elements are connected to.

From the above disclosure it should be apparent that the invention fully achieves the intended aim and objects.

In particular, the slanted or inclined arrangement of the band elements provides great advantages both from a functional and from a production standpoint.

The invention, as disclosed, is susceptible to several modifications and variations, all of which will come within the scope of the invention.

Moreover, all of the constructional details, can be replaced by other technically equivalent elements.

In practicing the invention, the used

materials, provided that they are compatible to the intended application, as well as the contingent size and shapes, can be any, depending on requirements.

THIS PAGE BLANK (USPTO)

CLAIMS

1. A washing brush for washing brush assemblies to be applied to automatic systems for washing motor vehicles in general, comprising a cylindric body having a central longitudinal axis and a side cylindric outer surface, characterized in that on said cylindric outer surface are defined a plurality of separated adjoining diagonal seats having a length smaller than the diameter of said cylindric body, each for receiving fixedly therein a cleaning band element, that said separated seats are inclined with respect to said central longitudinal axis, and that with said cylindric body in a vertical and non driven condition thereof, each said band element will fall so as to overlap on an adjoining like band element.

2. A washing brush, according to the preceding claim, characterized in that each said band element comprises an elongated substantially rectangular flat body having an end portion thereof fixedly restrained in a respective said seat of said cylindric body, each said band element being so longitudinally slit or cut as to define a plurality of adjoining substantially flat and parallel cleaning bristles, said bristles having different lengths.

3. A washing brush, according to one or more of the preceding claims, characterized in that said adjoining strips of the band elements have different colors, said colors defining a perfect epicycloidal color pattern.

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00053

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60S3/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 139 641 A (PARSEGHIAN GERARD A ET AL) 7 July 1964 (1964-07-07)	1-5,7
Y	column 4, line 42 - column 5, line 23; figures 5,13	6
Y	DE 201 14 359 U (WASH TEC HOLDING GMBH) 24 January 2002 (2002-01-24) abstract; figures	6
A	US 3 241 172 A (TILGNER RALPH F) 22 March 1966 (1966-03-22) the whole document	1-7
A	US 3 439 373 A (CLARK GAYLORD J) 22 April 1969 (1969-04-22) the whole document	1-7
-/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

18 June 2003

Date of mailing of the international search report

26/06/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gavaza, B.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 03/00053

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 0092, no. 86 (M-429), 13 November 1985 (1985-11-13) & JP 60 128050 A (WAI KEI GIKEN:KK), 8 July 1985 (1985-07-08) abstract; figures	1-7
A	DE 199 07 441 A (VORBACH HARALD) 31 August 2000 (2000-08-31) abstract; figures	1-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 03/00053

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3139641	A	07-07-1964	NONE	
DE 20114359	U	24-01-2002	DE 20114359 U1 WO 03018375 A1	24-01-2002 06-03-2003
US 3241172	A	22-03-1966	NONE	
US 3439373	A	22-04-1969	NONE	
JP 60128050	A	08-07-1985	JP 1052222 B JP 1566468 C	08-11-1989 25-06-1990
DE 19907441	A	31-08-2000	DE 19907441 A1	31-08-2000

60000 4000 10 3000 2000

THIS PAGE BLANK (USPTO)